

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



Europäisches Patentamt

European Patent Office

Office européen des brevets

⑪ Publication number: **0 445 093 B1**

⑫

EUROPEAN PATENT SPECIFICATION④⑤ Date of publication of patent specification :
20.07.94 Bulletin 94/29⑤① Int. Cl.⁵: **B01D 21/00, A61C 17/00**②① Application number : **91850032.3**②② Date of filing : **12.02.91**⑤④ **Settling apparatus.**③⑩ Priority : **14.02.90 SE 9000524**④③ Date of publication of application :
04.09.91 Bulletin 91/36④⑤ Publication of the grant of the patent :
20.07.94 Bulletin 94/29⑧④ Designated Contracting States :
AT BE CH DE DK ES FR GB GR IT LI LU NL SE⑤⑥ References cited :
EP-A- 0 096 670
FR-A- 1 568 571
GB-A- 1 238 489
US-A- 2 613 811
US-A- 3 613 889
US-A- 4 151 075
US-A- 4 529 383⑦③ Proprietor : **STIFTELSEN CENTRUM FÖR**
DENTALTEKNIK OCH BIOMATERIAL I
HUDDINGE
Institutionsvägen 6
Plan 7
S-141 04 Huddinge (SE)⑦② Inventor : **Sundström, Gustaf Folke**
Burevägen 7
S-182 63 Djursholm (SE)⑦④ Representative : **Hynell, Magnus**
Hynell Patenttjänst AB
Box 236
S-683 02 Hagfors (SE)**EP 0 445 093 B1**

Note : Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

This invention relates to a settling apparatus for removing amalgam from waste water produced in a dental procedure, comprising an inclined passage having an inclination to the horizontal of from about 3° to 15°; a plurality of tubes having circular cross section, extending through said passage, substantially all of the tubes contacting other tubes in a side-by-side manner and forming channels therebetween; and means for flowing said waste water from a lowermost end of said passage, through said tubes in laminar flow and out of said passage, wherein amalgam in said waste water is settled in said tubes.

BACKGROUND OF THE INVENTION

Several different embodiments of settling apparatus comprising a plurality of parallel and inclined settling canals separated by lamellar elements are known to the art. By way of example may be mentioned those apparatuses which are described in the U.S. patents Nos. 2,868,384, 3,494,475, 3,741,892, and in the German patent No. 3 010 365. It is also known to utilize tubular settling channels, according to Swedish patent No. 352 243. Those apparatus which so far have been used in practice, however, have not satisfactorily met the specific demands which are required for settling apparatus intended for the separation of amalgam from waste water in dentists' practices, i.e. for applications where there is a comparatively small flow of water. The known apparatus either have been designed for very large installations and to comply with those specific demands which are raised in connection with such large installations, or they do not have satisfactory separation efficiency. GB-A-1 238 489 describes a settling apparatus of said large size type. US-A-4 529 383 relates to a gravity separator for use in dental suction apparatus. FR-A-1 568 571 describes a rotary- and labyrinth type of separator. EP-A-0 096 670 relates to a filter apparatus for separating for example amalgam from waste water. US-A-2 613 811 describes a continuous settling apparatus.

BRIEF DESCRIPTION OF THE INVENTION

The purpose of the invention is to provide a small, handy apparatus which can satisfy the specific demands which are required for apparatus for the separation of amalgam from the waste water from a dentist's practice or the like. Among these demands may be mentioned that the apparatus must have small dimensions, be inexpensive and simple to use, and have a very high separation efficiency as far as amalgam is concerned.

It is also a purpose of the invention that the apparatus, when it has been filled with removed amalgam to a certain degree, shall be readily reconditioned for further use.

These and other objects may be achieved therein

that the apparatus comprises in series, and in fluid connection with each other, a presettling chamber, an inlet chamber to said inclined passage, and said inclined passage;

that said inclined passage has at least a bottom wall extending in the longitudinal direction of the passage, and an end wall (13, 46) in the inlet end of the passage;

that said end wall consists of a perforated partition wall provided between said inlet chamber and said inclined passage;

that the inclined passage has a cross-section of between 2000 and 20000 mm²;

that the tubes extend in said inclined passage parallel to said bottom wall, resting at their lowermost ends against said perforated partition wall;

that the inclined passage and the tubes resting against the perforated partition wall have a length of about 100-400 mm; and

that the tubes have an internal diameter of between 1 and 4 mm, and a wall thickness of not more than 0.5 mm,

wherein amalgam may be deposited by settling or by direct contact not only on the interior, but also on the exterior of the tubes.

Preferably the passage and hence the tubes have an inclination of 5-10°.

According to a preferred embodiment the settling apparatus comprises a pre-settling chamber, which has a larger volume than the inclined passage which contains the tubes, and the inclined passage, according to a preferred embodiment, is part of a separate unit or cassette which can be removed from and replaced in the main part of the apparatus. By exchange of cassettes the apparatus can be reconditioned quickly when the tubes and the passage between the tubes have been loaded with amalgam to a predetermined degree. The exchange of cassettes may, for example, be made regularly and rather frequently according to a certain time schedule, while the cleaning of the larger pre-settling chamber may be performed less frequently. The cassette may consist of a cylindrical barrel in the form of a thicker outer tube, which, at least in that end thereof

which is lowermost when the cassette is mounted in or on the settling apparatus, is provided with a bottom plate against which the narrow tubes may rest inside the thicker outer tube. In fluid communication with this bottom plate there may be provided a pre-chamber which communicates with the pre-settling chamber.

5 Further, according to another embodiment of the invention, the exterior of the apparatus may consist of a housing having upper and lower compartments, with the upper and lower compartments being separated from each other by an inclined partition wall. The inclination of the inclined partition wall is equal to the inclination of the inclined passage, which is provided in the lower compartment beneath the inclined partition wall, together with an inlet chamber for the inclined passage. The upper compartment defines a pre-settling chamber and a conduit is provided through the inclined partition wall in the lower part thereof between the pre-settling chamber in the upper compartment and the inlet chamber in the lower compartment. According to this embodiment, the tubes in the inclined passage rest directly or indirectly on support members provided in the lower compartment.

15 Further features and aspects of the invention will be apparent from the appending claims and from the following description of a preferred embodiments.

BRIEF DESCRIPTION OF DRAWINGS

20 In the following description of preferred embodiments reference will be made to the accompanying drawings, in which

- Fig. 1 is a side view of a settling apparatus according to a first preferred embodiment;
- Fig. 2 is an end view of Fig. 1;
- Fig. 3 shows a cross-sectional view of a settling cassette forming part of the settling apparatus, along the line III-III in Fig. 1;
- 25 Fig. 4 shows a cross-sectional view of the settling cassette along the line IV-IV in Fig. 3;
- Fig. 4A shows enlarged details of Fig. 4;
- Fig. 5 is a top view of a settling apparatus according to a second preferred embodiment; and
- Fig. 6 shows a vertical section through the settling apparatus along the lines VI-VI in Fig. 5.

30 With reference to Fig. 1 and Fig. 2 the main part of the settling apparatus according to the first embodiment is designated 1. In this main part there is a pre-settling chamber 2 having an inlet conduit 3 and an outlet conduit 4 for waste water. Further there is provided a clean-out lid 5 on one side of the pre-settling chamber.

On the other side of the main part 1 there is provided an inclined recess 6, in which there is provided a removable cassette 7, which is secured in the recess 6 by means of a pair of rubber bands 8. The inclination of the recess 6 defines the inclination of the cassette 7, which is, in a most preferred embodiment, about 7° to the horizontal plane.

35 The cassette 7 consists of an outer cylindrical barrel 9, which according to the embodiment has a circular cross section, although a rectangular and other cross-sections may be used. In each end of the barrel 9 there is a cap, e.g. a screw cap 10 and 11, respectively. As shown in Figure 3, fastened between circular abutment surface 12 on the inside of caps 10 and 11, respectively, and the outside of barrel 9 are perforated plates, e.g. circular wire screens 13 and 14, respectively. Between these screens 13, 14 and the end portions of the caps 10 and 11 there is provided a lower inlet pre-chamber 15, and an upper end chamber 16, respectively.

40 The interior, inclined passage 9A (see Figures 4 and 4A) of the barrel 9 is filled with a plurality of small diameter, narrow, thin-walled plastic tubes 17, which are in a number that they contact each other in a side-by-side manner and in a more or less regular pattern and extend through the barrel 9, so that channels are formed between the tubes. The sizes of these channels may vary somewhat depending on irregularities in the arrangement of the tubes and also on the number of tubes, i.e. on how closely the tubes are packed. According to a preferred embodiment the tubes have a diameter of about 2.5 mm and a wall thickness of 0.5 millimeter or less, e.g. only a few tenths of a millimeter, i.e. a thickness which can be neglected with regard to the cross-section of passage 9A. The tubes 17 rest at their lowermost ends against the lower screen 13.

50 Preferably the tubes 17 have the same length as the barrel 9 and are secured between the two screens 13 and 14. The previously mentioned outlet conduit 4 from the pre-settling chamber 2 is connected to an inlet opening 20 of the lower inlet pre-chamber 15, and a discharge conduit 21 for clarified water is connected to a discharge opening 22 in the end wall of the upper end-chamber 16.

55 When the settling apparatus is in use, waste water containing amalgam is flowed through the conduit 3 to the pre-settling chamber 2. Larger lumps of amalgam, tooth chips and other larger solid objects have been separated from this waste water by screening in a previous operation. The main part of remaining amalgam is deposited on the bottom of the pre-settling chamber 2. From the pre-settling chamber 2 the water is flowed to the cassette 7. In the inclined passage 9A in the cassette 7 the water is caused to flow slowly upwards from the pre-chamber 15 through the screen 13, and further through the large number of tubes 17 as well as through

the spaces 18 between these tubes 17 and up to the upper end-chamber 16 and further out through the discharge conduit 21. Due to the facts that the tubes 17 are narrow and that water also passes between the tubes in the spaces 18, laminar flow of the water is achieved. The laminar flow in combination with the low flow speed of the water and the small inclination, preferably about 7°, of cassette will cause even extremely small amalgam particles to be deposited by settling or by direct contact on the exterior, as well as on the interior, surfaces of the walls of the tubes 17. The flow of the waste water through the apparatus may be caused by any convenient means, such as by gravity, by syphon action, by pumps or the like.

When the cassette 7 has been filled with amalgam to a certain degree or when the settling process has been conducted for a certain pre-determined period of time, the cassette 7 is removed and is replaced by a new cassette containing clean tubes 17. The used cassette is sent to a commercial plant for recovery of the amalgam. At certain intervals, also the pre-settling chamber 2 is cleaned with respect to the amalgam which has been collected in pre-settling chamber 2.

With reference now to Fig. 5 and Fig. 6 a settling apparatus of a second embodiment is generally designated 30. All the parts of the apparatus are enclosed in a housing 31 consisting of two identical main parts, namely an upper half 32 of the housing, and a lower half 33. The two halves 32 and 33 consist of injection molded plastic material and may be made in the same molding tool or die which reduces the production cost. The two halves 32 and 33 are secured to each other along an inclined parting plane, for example, by clamping together the two halves along a circumferential edge portion of an inclined partition wall 34 in said inclined plane. The inclined partition wall 34 may consist of rubber or a polymeric material which may serve as a gasket between the two halves 32 and 33.

The inclined partition wall 34 has an inclination of between 3° and 15°, preferably between 5° and 10° or for example 7°, with respect to the horizontal. The compartment in the housing 31 above the inclined partition wall 34 constitutes a pre-settling chamber 35 and may correspond to 50% of the whole volume of the housing 31. The pre-settling chamber 35 has an inlet 36 in the top portion or roof 37 of the pre-settling chamber 35 in the region of the top portion which is nearer of the inclined partition wall 34. In the bottom part of the inclined partition wall 34 there is provided a communication conduit 38 extending through the partition wall, establishing fluid communication between the pre-settling chamber 35 and an inlet chamber 39 beneath the inclined partition wall 34. Further, vertical baffles 40A, 41A, 42A extend downwards from the roof 37 between the inlet conduit 36 and the communication conduit 38, the length of said baffles 40A, 41A, and 42A successively being longer in relation to the slope of the inclined partition wall 34, as shown in Figure 6.

In the bottom compartment defined by the lower half 33, which is preferably of the same size and configuration as the upper half 32, there are also vertical partition walls 40B, 41B, and 42B corresponding to the baffles 40A-42A in the upper compartment. The partition walls 40B-42B serve as supports for an inclined plate 43 which is parallel with the inclined partition wall and rests on said supports 40B-42B.

Between the inclined partition wall 34 and the inclined plate 43 there is an inclined passage 44 which has the same inclination as the inclined partition wall 34 and the inclined plate 43. The inclined passage 44 extends between the longitudinal side walls of the housing 31. In the lower end of the inclined passage 44 there is provided the inlet chamber 39 and in the upper end there is correspondingly provided an outlet chamber 45. The inlet chamber 39 is defined by a screen 46 which is integrated with top and bottom distance members 47 and 48, which contact the end wall of the housing 31. The outlet chamber 45 is correspondingly defined by a screen 50 and upper and lower space members 51 and 52, respectively. In the region of the outlet chamber 45 there is provided a discharge opening 53.

The passage 44 is filled with tubes 55 of the same type as have been explained in connection with the above described first embodiment. Like the tubes in the said first embodiment, the tubes 55 contact each other in a side-by-side manner so that, preferably, the whole volume of the passage 44 is filled with the tubes 55, and also so that channels are formed between the contacting tubes in a more or less regular pattern.

When the settling apparatus 30 is in use, water containing amalgam is fed through inlet 36 to the pre-settling chamber 35 where the main part of amalgam existing in the waste water is deposited on the inclined partition wall 34, wherein the baffles 40A, 41A, and 42A contribute to a flow pattern of water in the pre-settling chamber 35 which is advantageous to the settling procedure. From the pre-settling chamber 35 the waste water is fed via conduit 38 through the bottom part of the inclined partition wall 34 to the inlet chamber 39 beneath the lowermost part of the partition wall 34. From the inlet chamber 39 the waste water flows through the screen 46 and further through the large number of tubes 55 as well as through the channels between the tubes 55 and up to the outlet chamber 45 and out through the discharge conduit 53. In the inclined passage 44, which according to this embodiment has a rectangular cross section, the water will have laminar flow, as according to the previous embodiment, wherein even extremely small amalgam particles are deposited by settling or by direct contact on the exterior, as well as on the interior, surfaces of the walls of the tubes 55.

When the space 44 has been filled with amalgam to a certain degree or when the settling process has

been conducted for a certain predetermined period of time, the apparatus is demounted; amalgam which has collected in the pre-settling chamber 35 is removed, and the tubes 55 are replaced by new ones, which may be in a cassette form, whereafter the apparatus is re-assembled.

5

Claims

1. A settling apparatus for removing amalgam from waste water produced in a dental procedure, comprising
 10 an inclined passage (9A, 44) having an inclination to the horizontal of from about 3° to 15°; a plurality of tubes (17, 55) having circular cross section, extending through said passage, substantially all of the tubes contacting other tubes in a side-by-side manner and forming channels therebetween; and means for flowing said waste water from a lowermost end of said passage, through said tubes in laminar flow and out of said passage, wherein amalgam in said waste water is settled in said tubes, characterized in that the
 15 apparatus comprises in series, and in fluid connection with each other, a presettling chamber (2, 35), an inlet chamber (15, 39) to said inclined passage, and said inclined passage; that said inclined passage has at least a bottom wall (43) extending in the longitudinal direction of the passage, and an end wall (13, 46) in the inlet end of the passage; that said end wall consists of a perforated partition wall (13, 46) provided between said inlet chamber and said inclined passage;
 20 that the inclined passage has a cross-section of between 2000 and 20000 mm²; that the tubes extend in said inclined passage parallel to said bottom wall, resting at their lowermost ends against said perforated partition wall; that the inclined passage and the tubes resting against the perforated partition wall have a length of about
 25 100-400 mm; and that the tubes have an internal diameter of between 1 and 4 mm, and a wall thickness of not more than 0.5 mm, wherein amalgam may be deposited by settling or by direct contact not only on the interior, but also on the exterior of the tubes.
2. Apparatus according to claim 1, wherein the inclined passage forms part of a cassette (7), which can be removed from the main part of the settling apparatus.
3. Apparatus according to claim 2, wherein said main part contains said presettling chamber (2).
- 35 4. Apparatus according to claim 1, wherein the apparatus includes a housing (31) having upper and lower compartments separated from each other by an inclined partition wall (34), the inclination of said inclined partition wall being equal to the inclination of said inclined passage (44), and wherein the inclined passage is disposed in the lower compartment and beneath said inclined partition wall and an inlet chamber (39) for said inclined passage is in fluid communication with said passage, and wherein the upper compartment defines a pre-settling chamber (35), and a conduit (38) is provided through said inclined partition wall (34) in the lowermost part thereof between the pre-settling chamber in the upper compartment and the inlet chamber in the lower compartment.
- 40 5. Apparatus according to claim 4, wherein the circumferential edge portion of the inclined partition wall is clamped between an upper half (32) of the housing defining said upper compartment and a lower half (33) of the housing defining said lower compartment, and wherein the inclined partition wall also serves as a gasket between said upper and lower halves.
- 45 6. Apparatus according to claim 4, wherein the inclined passage (44) is supported on members (40B, 41B, 42B) provided in said lower compartment.
- 50 7. Apparatus according to claim 6, wherein vertical partition walls (40A-42A, 40B-42B) are provided in the upper and lower compartments, extending downwardly from a roof (37) of the upper compartment and upwards from a bottom of the lower compartment, respectively, and an inlet conduit (36) to said pre-settling chamber is provided in the part of the pre-settling chamber which is opposite that part where said conduit (38) between the pre-settling chamber and said inlet chamber is located, said partition walls in the upper compartment serving as baffle-members in the pre-settling chamber, and said partition walls in the lower compartment serving as support members for said inclined passage, the vertical length of said vertical partition walls in the pre-settling chamber increasing with the slope of the inclined partition

55

wall from the inlet conduit (36) to the said conduit from the pre-settling chamber to the inlet chamber (39), and the vertical length of said vertical partition walls in the lower compartment increasing along the length of the inclined passage in relation to the inclination of the inclined partition wall.

5

Patentansprüche

1. Absetzvorrichtung zum Entfernen von Amalgam aus Abwasser, das bei Denalarbeiten anfällt, umfassend einen gegenüber der Horizontalen um etwa 3° bis 15° geneigten Durchlaß (9A), (44), durch den sich eine Vielzahl von Röhren (17), (55) mit kreisförmigem Querschnitt erstreckt, die sich nahezu alle seitlich berühren, so daß zwischen ihnen Kanäle ausgebildet werden, sowie Einrichtungen, die bewirken, daß das genannte Abwasser vom untersten Ende des genannten Durchlasses laminar durch die genannten Röhren zum Austritt des genannten Durchlasses strömt, wobei das in dem genannten Abwasser enthaltene Amalgam in den genannten Röhren abgesetzt wird, dadurch gekennzeichnet, daß das Gerät in Reihenschaltung und jeweils miteinander in Flüssigkeitskontakt stehend eine Vorabsetzkammer (2, 35), eine Eintrittskammer (15, 39) zu dem genannten geneigten Durchlaß sowie den genannten Durchlaß aufweist; daß der genannte geneigte Durchlaß zumindest eine sich in Längsrichtung durch den Durchlaß erstreckende Bodenwand (43) sowie eine Endwand (13, 46) an der Eintrittsseite des Durchlasses aufweist; daß die genannte Endwand aus einer perforierten Trennwand (13, 46) zwischen der genannten Eintrittskammer und dem genannten geneigten Durchlaß besteht; daß der geneigte Durchlaß einen Querschnitt aufweist, der zwischen 2 000 und 20 000 mm² beträgt; daß die Röhren in dem geneigten Durchlaß parallel zu der genannten Bodenwand verlaufen, wobei ihre unteren Enden an der genannten perforierten Trennwand anliegen; daß die Länge des geneigten Durchlasses und der an der perforierten Trennwand anliegenden Röhren etwa 100 bis 400 mm beträgt; und daß die Röhren einen Innendurchmesser zwischen 1 und 4 mm und eine Wandstärke von höchstens 0,5 mm aufweisen, wobei das Amalgam durch Absetzen oder durch direkten Kontakt nicht nur an den Innen-, sondern auch an den Außenseiten der Röhren abgeschieden werden kann.
2. Vorrichtung gemäß Anspruch 1, bei welcher der geneigte Durchlaß Teil einer Kassette (7) ist, die vom Hauptteil der Absetzvorrichtung entfernt werden kann.
3. Vorrichtung gemäß Anspruch 2, bei welcher der genannte Hauptteil die genannte Vorabsetzkammer (2) enthält.
4. Vorrichtung gemäß Anspruch 1, welche aus einem Gehäuse (31) besteht, das eine obere und eine untere Kammer aufweist, die durch eine geneigte Scheidewand (34) voneinander getrennt sind, deren Neigungswinkel dem des genannten geneigten Durchlasses (44) entspricht und bei welcher sich der geneigte Durchlaß in der unteren Kammer unterhalb der genannten geneigten Scheidewand befindet, wobei eine Eintrittskammer (39) für den genannten Durchlaß mit diesem in Flüssigkeitsverbindung steht, und bei welcher die obere Kammer eine Vorabsetzkammer (35) bildet, wobei durch den untersten Teil der genannten geneigten Scheidewand (34) ein Verbindungsrohr (38) verläuft, das die Vorabsetzkammer in der oberen Gehäusehälfte mit der Eintrittskammer in der unteren Gehäusehälfte verbindet.
5. Vorrichtung gemäß Anspruch 4, bei welcher die in Umfangsrichtung verlaufende Kante des geneigten Trennsteges zwischen einer oberen Hälfte (32) des Gehäuses, die die genannten obere Kammer bildet, und einer unteren Hälfte (33) des Gehäuses, die die genannte untere Kammer bildet, festgeklemt wird und bei welcher die geneigte Scheidewand auch als Dichtung zwischen der genannten oberen und unteren Hälfte dient.
6. Vorrichtung gemäß Anspruch 4, bei welcher der geneigte Durchlaß (44) auf Stützen (40B), (41B), (42B), in der genannten unteren Kammer aufliegt.
7. Vorrichtung gemäß Anspruch 6, bei welcher sich in der oberen und in der unteren Kammer senkrechte Scheidewände (40A-42A, 40B-42B) befinden, die sich vom Dachteil (37) der oberen Kammer nach unten bzw. vom Boden der unteren Kammer nach oben erstrecken, bei welcher sich ein Eintrittsstutzen (36) für die genannte Vorabsetzkammer an dem Teil der Vorabsetzkammer, der dem Teil, an dem sich das genannte Verbindungsrohr (38) zwischen Vorabsetzkammer und der genannten Eintrittskammer gegen-

überliegt, befindet, wobei die genannten Scheidewände in der oberen Kammer als Leitelemente in der Vorabsetzkammer und die genannten Scheidewände in der unteren Kammer als Tragelemente für den genannten geneigten Durchlaß dienen und wobei die vertikale Länge der genannten vertikalen Scheidewände in der Vorabsetzkammer entsprechend dem Neigungswinkel der geneigten Scheidewand vom Eintrittsstutzen (36) in Richtung des genannten Verbindungsrohres zwischen Vorabsetzkammer und Eintrittskammer (39) ansteigt, während die vertikale Länge der genannten vertikalen Scheidewände in der unteren Kammer längs des geneigten Durchlasses gemäß dem Neigungswinkel des geneigten Trennsteges ansteigt.

Revendications

1. Dispositif de sédimentation pour éliminer l'amalgame de l'eau résiduaire produite lors d'une intervention dentaire, comprenant un passage incliné (9A,44) dont l'inclinaison par rapport à l'horizontale va de 3° à 15° ; plusieurs tubes (17,55) à section transversale circulaire, traversant ledit passage, pratiquement tous les tubes étant en contact avec d'autres tubes en étant côté à côté et en formant des canaux entre eux ; et un moyen pour l'écoulement de l'eau résiduaire depuis une extrémité inférieure du dit passage, à travers les dits tubes selon un écoulement laminaire, et hors du dit passage, dans lequel l'amalgame contenu dans l'eau résiduaire sédimente dans les dits tubes ; caractérisé en ce que le dispositif comprend, en série et en liaison de fluide l'un avec l'autre, une chambre de pré-sédimentation (2,35), une chambre d'entrée (15,39) dans le dit passage incliné, et le dit passage incliné ; en ce que le dit passage incliné présente au moins une paroi inférieure (43) orientée dans la direction longitudinale du passage, et une paroi d'extrémité (13,46) à l'extrémité intérieure du passage ; en ce que la dite paroi d'extrémité est constituée par une paroi de séparation perforée (13,46) prévue entre la dite chambre d'entrée et le dit passage incliné ; en ce que le passage incliné présente une section transversale comprise entre 2000 et 20000 mm² ; en ce que les tubes sont orientés à l'intérieur du dit passage incliné parallèlement à la dite paroi inférieure, en reposant à leurs extrémités inférieures contre la dite paroi de séparation perforée ; en ce que le passage incliné et les tubes reposant contre la paroi de séparation perforée ont une longueur d'environ 100-400 mm ; et en ce que les tubes présentent un diamètre intérieur compris entre 1 et 4 mm, et une épaisseur de paroi qui n'est pas supérieure à 0,5 mm ; dans lequel l'amalgame peut se déposer par sédimentation ou par contact direct non seulement sur l'intérieur des tubes, mais aussi sur l'extérieur de ceux-ci.
2. Dispositif selon la revendication 1, dans lequel le passage incliné constitue une partie d'une cassette (7), qui peut être séparée de la partie principale du dispositif de sédimentation.
3. Dispositif selon la revendication 2, dans lequel la dite partie principale contient la dite chambre de pré-sédimentation (2).
4. Dispositif selon la revendication 1, dans lequel le dispositif comprend un logement (31) présentant des compartiments supérieur et inférieur séparés l'un de l'autre par une paroi de séparation inclinée (34), l'inclinaison de la dite paroi de séparation inclinée étant égale à l'inclinaison du dit passage incliné (44), et dans lequel le passage incliné est disposé dans le compartiment inférieur et au dessous de la dite paroi de séparation inclinée et une chambre d'entrée (39) dans le dit passage incliné étant en communication de fluide avec le dit passage, et dans lequel le compartiment supérieur détermine une chambre de pré-sédimentation (35), et un conduit (38) est ménagé à travers la dite paroi de séparation (34) à la partie inférieure de celle-ci, entre la chambre de pré-sédimentation contenue dans le compartiment supérieur et la chambre d'entrée contenue dans le compartiment inférieur.
5. Dispositif selon la revendication 4, dans lequel le bord périphérique de la paroi de séparation inclinée est serré entre une moitié supérieure (32) du logement déterminant le dit compartiment supérieur et une moitié inférieure du logement déterminant le dit compartiment inférieur, et dans lequel la paroi de séparation inclinée sert aussi de joint entre les dites moitiés supérieure et inférieure.
6. Dispositif selon la revendication 4, dans lequel le passage incliné (44) est supporté par des éléments (40B, 41B, 42B) ménagés dans ledit compartiment inférieur.

7. Dispositif, selon la revendication 6, dans lequel des parois de séparation verticales (40A-42A, 40B-42B) sont prévues dans les compartiments supérieur et inférieur, en s'étendant vers le bas depuis un toit (37) du compartiment supérieur et vers le haut depuis un fond du compartiment inférieur, respectivement, et un conduit (36) d'entrée dans la chambre de pré-sédimentation est ménagé dans la partie de la chambre de pré-sédimentation qui est à l'opposé de la partie où est situé le conduit reliant la chambre de pré-sédimentation et la dite chambre d'entrée, les dites parois de séparation du compartiment supérieur servant d'éléments défecteurs dans la chambre de pré-sédimentation, et les dites parois de séparation du compartiment inférieur servant d'éléments de support pour le dit passage incliné, la longueur verticale des dites parois de séparation de la chambre de pré-sédimentation augmentant avec la pente de la paroi de séparation inclinée du conduit d'entrée (36) vers le dit conduit reliant la chambre de pré-sédimentation à la chambre d'entrée (39), et la longueur verticale des dites parois de séparation verticales du compartiment inférieur augmentant le long du passage incliné en relation avec l'inclinaison de la paroi de séparation inclinée.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 4A.




Fig. 5.




Fig. 6.

